

# V9 VENTED HARD HAT

PRODUCT CODE: HHV9\_(COLOUR)



HHV9\_W



HHV9\_BK



HHV9\_B



HHV9\_FP



HHV9\_FY



HHV9\_G



HHV9\_GY



HHV9\_FO



HHV9\_O



HHV9\_R



HHV9\_Y

## FEATURES

- Complete with 9 ventilation points
- Lightweight ABS plastic vented hard hat
- Extended peak and rain gutter
- Replaceable cotton sweatband
- 25mm moulded earmuff slots to accommodate Pro Choice hearing protection
- Fits all head sizes: 53cm - 66cm
- 6 point 25mm webbing harness
- PushLock harness adjustment
- Functional sizing harness to improve fit and comfort
- Distinguish workers on site by utilising our pad printing or vinyl cut print services that can customise hard hats before delivery
- Replacement harness code: HHHPL-V9

## SPECIFICATIONS

**Helmet Material:** ABS Plastic

**Harness Materials:** HDPE/Polyester

**Weight:** 362g

**Size:** 53cm - 66cm

**Colours:** Black, Blue, Fluoro Orange, Fluoro Pink, Fluoro Yellow, Green, Grey, Orange, Red, White, Yellow

## PACKAGING

**Unit:** Each | **Carton:** 20

## APPLICATIONS

- Agriculture
- Aviation
- Automotive
- Chemical manufacturing
- Construction
- Heavy engineering
- Metal processing
- Mining and quarrying
- Welding
- Woodworking

## CARE INSTRUCTIONS

Pro Choice hard hats should be inspected for any deterioration or damage prior to use. If any cracks, colour distortion or deep abrasions are found, the hard hat should be disposed of.

Industry recommends the hard hat shell to be replaced after 3 years of working life, the harness before 2 years of use and the sweatband as required.

To extend the working life of your hard hat, avoid excessive exposure to UV and any solvents. Clean your hard hat and harness with warm soapy water on a regular basis.

## STANDARDS

**AS/NZS 1801:1997** Type 1 Industrial Occupational Protective Helmets

**AS/NZS 1800:1998** Occupational Protective Helmets - Selection, Care and Use

